

# PRS30

APPLICATION  
Residential/Commercial

MODELS  
Shrub, 4", 6", 12"

**KEEP WATER PRESSURE AT A TRUE 30 PSI FOR COMMERCIAL SITES TO REDUCE WASTE AND MAXIMIZE PERFORMANCE.**

## FEATURES

- Application: Residential/commercial
- Models: Shrub, 4", 6", 12"
- No side inlet (NSI) version available in 6" and 12"
- Warranty period: 5 years

## ADVANCED FEATURES

- Identification cap is brown for easy field ID
- Pressure regulated to 30 PSI
- Co-molded wiper seal with UV resistant material
- Body cap won't leak under high pressure
- Drain check valve (optional)
- Heavy-duty retraction spring
- Innovative directional flush plug design
- Reclaimed purple body cap (optional)
- Compatible with all female threaded nozzles

## OPERATING SPECIFICATIONS

Recommended pressure range:  
15 to 100 PSI

## FACTORY INSTALLED OPTIONS

Drain check valve (up to 14' of elevation)  
Reclaimed water ID cap

## USER INSTALLED OPTIONS

Vandal-proof cap (P/N PROS-PRS30-VPC)  
Drain check valve (up to 14' of elevation; P/N 457400)  
Reclaimed water ID cap (P/N 458530)  
Snap-on reclaimed cover (P/N PROSRCCAP)

PRS30 formerly Institutional Spray



PRESSURE  
REGULATED AT  
**30** PSI



**PROS-00-PRS-30:**  
Inlet size: 1/2" Female NPT



**PROS-04-PRS30:** Overall height: 5 7/8"  
Exposed diameter: 2 1/4"  
Inlet size: 1/2" Female NPT



**PROS-06-PRS30:** Overall height: 8 3/4"  
**PROS-06-PRS30-NSI (right)**  
Exposed diameter: 2 1/4"  
Inlet size: 1/2" Female NPT



**PROS-12-PRS30:** Overall height: 16 1/2"  
**PROS-12-NSI-PRS30 (right)**  
Exposed diameter: 2 1/4"  
Inlet size: 1/2" Female NPT

WORKS BEST WITH

PRO-SPRAY FIXED  
ARC NOZZLES

PRO ADJUSTABLE  
NOZZLES



## SPECIFICATIONBUILDER

[www.hunterindustries.com/PRS30](http://www.hunterindustries.com/PRS30)

PRS30 MODELS (formerly Institutional Spray)	OPTIONS
PROS-00-PRS30 = 30 PSI regulated shrub adapter	(blank) = No option
PROS-04-PRS30 = 30 PSI regulated 4" pop-up	CV = Factory-installed drain check valve (pop-up models only)
PROS-06-PRS30 = 30 PSI regulated 6" pop-up	CV-R = Factory-installed drain check valve and reclaimed body cap (shrub molded in purple)
PROS-06-NSI-PRS30 = 30 PSI regulated 6" pop-up with no side inlet	
PROS-12-PRS30 = 30 PSI regulated 12" pop-up	6" and 12" models ordered as CV will come as no side inlet
PROS-12-NSI-PRS30 = 30 PSI regulated 12" pop-up with no side inlet	

### EXAMPLES

<b>PROS-04-PRS30</b>	4" pop-up regulated at 30 PSI
<b>PROS-06-PRS30 - CV - 12H</b>	6" pop-up regulated at 30 PSI, drain check valve, and 12' half circle nozzle
<b>PROS-12-PRS30 - CV-R - 10A</b>	12" pop-up regulated at 30 PSI, drain check valve, reclaimed body cap, and 10' adjustable nozzle