

MP ROTATOR®

Radius: 8' to 35'

FEATURES

- Matched precipitation at any arc or radius setting
- Radius can be reduced up to 25% on all models
- Easy arc adjustment
- Color-coded for easy identification
- Double-pop feature keeps dirt and debris out of nozzle
- Removable filter screen ensures hassle-free service
- Avoid runoff with low precipitation rate
- Wind-resistant multi-stream technology
- High distribution uniformity
- ▶ Automatic matched precipitation
- ▶ Double-pop

OPERATING SPECIFICATIONS

- Recommended operating pressure: 40 PSI

OPTIONS

- Specify Pro-Spray® PRS40 pop-up for accurate pressure regulation at 40 PSI
- Adding "HT" will specify male threaded nozzles

▶ = Advanced Feature descriptions on page 35

MP1000 8' to 15' radius



MP1000-90
90° to 210°



MP1000-210
210° to 270°



MP1000-360
360°

MP2000 13' to 21' radius



MP2000-90
90° to 210°



MP2000-210
210° to 270°



MP2000-360
360°

MP3000 22' to 30' radius



MP3000-90
90° to 210°



MP3000-210
210° to 270°



MP3000-360
360°

MP3500 31' to 35' radius



MP3500-90
90° to 210°

MP ROTATOR – SPECIFICATION BUILDER: ORDER 1 + 2

1 Model	2 Options
MP1000-90 = 8' to 15' radius, adjustable from 90° to 210°	(blank) = No option HT = Male threaded version <i>(Not available in 3500)</i>
MP1000-210 = 8' to 15' radius, adjustable from 210° to 270°	
MP1000-360 = 8' to 15' radius, 360°	
MP2000-90 = 13' to 21' radius, adjustable from 90° to 210°	
MP2000-210 = 13' to 21' radius, adjustable from 210° to 270°	
MP2000-360 = 13' to 21' radius, 360°	
MP3000-90 = 22' to 30' radius, adjustable from 90° to 210°	
MP3000-210 = 22' to 30' radius, adjustable from 210° to 270°	
MP3000-360 = 22' to 30' radius, 360°	
MP3500-90 = 31' to 35' radius, adjustable from 90° to 210°	
MPLCS515 = Left corner strip, 5' x 15'	
MPRCS515 = Right corner strip, 5' x 15'	
MPSS530 = Side strip, 5' x 30'	
MPCORNER = 8' to 15' radius, adjustable from 45° to 105°	

Examples:

MP1000-210 = 8' to 15' radius, adjustable from 210° to 270°
PROS-06 - PRS40-CV - MP2000-90 = 6" pop-up regulated at 40 PSI, drain check valve, with MP 2000 90