# **FX**Luminaire.




The PB is a compact LED wall wash lighting solution. Available in 1 or 3 LED with full color lens options of frosted, blue, amber, and green included. The wider angle of the PB allows a broader lighting option for larger structures and spaces. Engineered with solid construction, yet petite in size.

# PB: Up Light

NUMBER OF LEDS:	1	3	ZDC
HALOGEN LUMEN EQUIVALENT:	10 Watt	20 Watt	10 Watt
USEFUL LED LIFE (L70):	50,000 hrs avg	50,000 hrs avg	50,000 hrs avg
INPUT VOLTAGE:	10 to 15V	10 to 15V	11 to 15V
VA TOTAL*:	2.4	4.5	7.2
WATTS USED:	2.0	4.2	6.0
LUMENS PER WATT (EFFICACY):	34	39	37
TOTAL LUMENS:	67	160	122
CRI (Ra):	83	82	83
CBCP (CENTER BEAM CANDLE POWER):	37	93	122
ССТ			
AMBER FILTER	2700K	2700K	N/A
FROSTED FILTER	3900K	3900K	N/A
GREEN FILTER	4500K	4500K	N/A
BLUE FILTER	5200K	5200K	N/A

 $<sup>\</sup>ensuremath{^*}$  (Use this number to size the transformer)





# PB: Up Light

# **FACTORY INSTALLED OPTIONS:** Order 1 + 2 (optional) + 3 + 4

Step	Description (	Code
1	FIXTURE	РВ
2	LUXOR OPTION	ZD, ZDC <sup>†</sup> (Color)
3	LAMP	1LED, 3LED,†
4	FINISH	AB*, AT*, NP*, BS, WG, FW, AL, BZ, DG, WI, SB, FB

# EXAMPLE: PB-ZD-3LED-AT = PB - ZD Option - 3LED Board - Antique Tumbled Finish


# FIELD INSTALLED OPTIONS: Order Individually

Mounting Options	
Super Slot Spike (753900) 2" x 8"	<b>Wall Plate: 1-gang</b> (WP-1G-050-XX**) 3.4" x 5.1"
Long Slot Spike (250015840000) 2.5" x 10"	Wall Plate: Round (WP-RD-050-XX**) 5" Diam.
<b>SuperJ-Box</b> (SJ-XX**) 2.5" x 11"	Coupling: Straight (COUP-XX**) 1.3" $\times$ 2.0"
Post Mount (PM-XX**) 2.5" x 13"	Coupling: 90-deg (ELBW-050-XX**) 1.3" x 2.0"
Mini J-Box ( <i>MJ-050-XX**</i> ) 3.5" x 1.3"	Coupling: T-mount (TMNT-050-XX**) 3.0" x 2.2"
TreeBox (TB-XX**) 5.4" x 1.9"	Riser (AL): Male Thread (YY-R-XX**)0.8" Diam., ½ NPSM
<b>Gutter Mount</b> ( <i>GM-SS</i> ) 4.0" x 4.0"	Riser (CU): Male/Female Threaded (YY-R-GT-XX**) 1.0" Diam.,½ NPSM

### EXAMPLE: SJ-BS - Super J-Box - Natural Brass Finish

PB 1LED ILLUMINANCE AT A DISTANCE

## **PHOTOMETRICS:**





#### **METALS**



**AB** = Antique Bronze\* (On Brass)



**AT** = Antique Tumbled\* (On Brass)



**NP** = Nickel Plate\*



**BS** = Natural Brass

## **POWDER COAT**



**WG** = White Gloss



**FW** = Flat White



 $\mathbf{AL} = \mathsf{Almond}$ 



**BZ** = Bronze Metallic



**DG** = Desert Granite



**WI** = Weathered Iron





**SB** = Sedona Brown



FB = Flat Black

The PB includes choice of LED board, choice of finish, 4 ft lead wire and a Long Slot Spike.



All PB up lights come standard with amber, green, blue and frosted filters

\* May require longer lead time \*\* Denotes finish option



Beam angle is calculated using LM-79 method for SSL Luminaires: "Beam angle is defined as two times the vertical angle at which the intensity is 50% of the maximum."

<sup>&</sup>lt;sup>†</sup> Fixtures specified with ZDC Technology™ are available only in one circuit board configuration. Do not specify a number of LEDs when ordering.