
FXLuminaire.



The PS represents the next generation of fixed-mount LED down lights. It is designed for top-mounting, and is available with an optional copper cover. The PS works with 1, 3, 6 or 9LED boards and is available in all of our metal and powder coat finishes. A mounting bracket is included for installation.

PS: Down Light

NUMBER OF LEDS:	1	3	6	9	ZDC
HALOGEN LUMEN OUTPUT EQUIVALENT:	10 Watt	20 Watt	35 Watt	50 Watt	20 Watt
USEFUL LED LIFE (L70):	50,000 hrs avg	50,000 hrs avg	50,000 hrs avg	50,000 hrs avg	50,000 hrs svg
INPUT VOLTAGE:	10 to 15V				
VA TOTAL: (Use this number to size the transformer):	2.4	4.5	13.5	13.5	11.0
WATTS USED:	2.0	4.2	10.1	11.2	9.1
LUMENS PER WATT (EFFICACY)	35	52	43	46	33
MAX LUMENS:	66	202	367	397	57
CRI	82	80	79	78	83
CBCP	275	975	2022	2276	62





PS: Down Light

FACTORY INSTALLED OPTIONS: Order 1 + 2 (optional) + 3 + 4 (optional) + 5

Step	Description	Code	
1	FIXTURE	PS	
2	LUXOR OPTION	ZD, ZDC [†] (Color)	
3	LAMP	1LED, 3LED, 6LED, 9LED,†	
4	OPTIONAL HANGING BRACKET	HB (Hanging bracket; Powder coat colors only)	
5	FINISH	CU-AB, BS-AB, CU-AT, BS-AT, CU, NP, BS, WG, FW, AL, BZ, DG, WI, SB, FB	

EXAMPLE: PS-3LED-HB-BZ = PS - 3LED Board - Hanging Bracket Option - Bronze Metallic Finish
PS-ZDC-BS-AB = PS - ZDC Option - Antique Bronze Finish

FIELD INSTALLED OPTIONS: Order Individually

Beam Angle Lenses			
LENS OPTIONS	1LED	3LED	6/9LED
Diffuser 18° (Preassembled)	770600	771300	771600
Flood Lens 30-32° (1 notch)	1LEDFLLENS	3LEDFLLENS	9LEDFLLENS
Wide Flood Lens 56-58° (2 notches)	1LEDWFLLENS	3LEDWFLLENS	9LEDWFLLENS

PHOTOMETRICS:



Beam angle is calculated using LM-79 method for SSL Luminaires:

METALS



CU-AB = Antique Bronze**
(On Copper)



BS-AB = Antique Bronze* (On Brass)



CU-AT = Antique Tumbled**
(On Copper)



BS-AT = Antique Tumbled* (On Brass)



CU = Copper⁺



NP = Nickel Plate*



BS = Natural Brass

POWDER COAT



WG = White Gloss



FW = Flat White



AL = Almond



BZ = Bronze Metallic



DG = Desert Granite



WI = Weathered Iron





SB = Sedona Brown



FB = Flat Black

The PS includes your choice of LED board, choice of finish, 9 ft. lead wire and mounting bracket.



All PS down lights come standard with amber, green, blue and frosted filters

* May require longer lead time



+ Fixture is covered by a copper sleeve





Fixture with optional hanging bracket installed



[†] Fixtures specified with ZDC Technology™ are available only in one circuit board configuration. Do not specify a number of LEDs when ordering.

 $[&]quot;Beam\ angle\ is\ defined\ as\ two\ times\ the\ vertical\ angle\ at\ which\ the\ intensity\ is\ 50\%\ of\ the\ maximum."$